



WOODGUARD®

REVITALIZER



REVIVES AND CLEANS WOOD

REVIVES WOOD BY REMOVING OXIDIZED CELLS

DOES NOT ALTER WOOD

QUICK AND EASY TO APPLY

EXTERIOR

PRODUCT DESCRIPTION

WoodGuard® Revitalizer removes oxidized cells caused by time and weather giving wood a new lease of life.

WoodGuard® Revitalizer penetrates wood fibres and quickly eliminates the grey appearance, stains and dirt without affecting the woods aesthetics and colour.

WoodGuard® Revitalizer does not contain solvents or chlorinated components. The acid component of this product is present in many plants (bean, spinach, cocoa...), and also in wine.

WoodGuard® Revitalizer can be applied to dry or slightly damp wood.

ADVANTAGES AND CHARACTERISTICS

- Non flammable.
- Easy and quick to apply.
- Ready to use.
- Can be used on all species of wood and coatings.
- Water-based product
- Petroleum solvent-free.
- Revives greying woods.
- Efficient in 15 minutes.

USE

WoodGuard® Revitalizer can be used outdoors to clean paneling, garden furniture, woodwork, shutters, wood gratings, fences, deckings, terraces...

CONTAINERS

1 and 5 litres.

CHEMICAL NATURE

- Water-based product formulated with oxalic acid.

TECHNICAL DATA

Physical state at 20 °C	: Viscous liquid
Colour	: Clear
Odour	: Light
pH	: 2 ± 0.5
Boiling point [°C]	: 100°C
Relative density	: 1.04 ± 0.015
Solubility in water [vol/vol]	: Total
Flashpoint [°C]	: Not applicable
VOC rate	: < 50 g/L*

* Calculation based on the components' data.

HOW TO USE

- Use neat: do not dilute.
- Shake the product well before use.
- Always carry out a preliminary test.
- Generously apply to the wood to be treated.
- Always apply from top to bottom.
- In the event of application on furniture and intricate woodwork or small surface, apply little by little using a brush or a paintbrush.
- Allow the product to act for 10 to 15 minutes, and then rinse thoroughly with water until the product is fully eliminated.
- Scrubbing with a nylon brush may improve the effectiveness of the product.
- If necessary, reapply the product following the same procedure.
- Let the wood dry and apply a apply one of our products from the **WoodGuard®** or **WoodGuard® Color** range to protect wood.

APPLICATION TOOLS

- Apply with a brush.



COVERAGE

Coverage depends on the degree of soiling.
The following values are for guidance only:

5 to 8 m² / litre

CLEANING YOUR EQUIPMENT

- Tools and equipment should be cleaned with water immediately after use.

STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C.
- Shelf-life: 24 months from date of manufacture, in original unopened can.

RECOMMENDATIONS

- Do not apply in rainy or hot weather. Surface and air temperature should be between 5° - 30°C.
- Do not dilute or mix with other products.
- Corrosive product: it is recommended to wear safety goggles, gloves and protection clothing.
- Protect vegetation.
- **WoodGuard® Revitalizer** does not remove the green traces on autoclave wood.
- Rinse thoroughly with water before applying another coating.
- In case of brushing or rinsing with a high pressure washer, always follow the wood grain.
- Do not lay the wood to be treated onto surfaces in order to avoid it becoming soiled.
- **WoodGuard® Revitalizer** can be used on PVC surfaces
- If crystals appear after drying, rinse them away with water.

HEALTH AND SAFETY

- Breathing protection: No breathing protection equipment is required under normal use conditions with suitable ventilation.
- Hand protection: Wear chemical resistant gloves (neoprene, PVC).
- Skin protection: Wear long-sleeved protection clothing.
- Eye protection: Wear protective goggles.
- In case of ingestion: Do not induce vomiting. Contact a doctor or specialist.

KEEP OUT OF REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD INDUSTRY

Unit 2a • Spring hill Industrial Estate • Colliers Way • Arley
COVENTRY CV7 8HN

Tel: +44 (0)1676 541324

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 18/05/2012